


NAIS**HIGHLY SENSITIVE 1500 V FCC
SURGE WITHSTANDING
MINIATURE RELAY****DS-RELAYS****UL File No.: E57521 CSA File No.: LR26550**

- High sensitivity 200 mW pick-up power
100 mW pick-up power types available
- Latching types available
- High switching capacity: 60 W, 125 VA
- High breakdown voltage 1,500 V FCC surge between open contacts
1,000 V AC between open contacts
- DIP—1C type can be used with 14 pin IC socket
2C type can be used with 16 pin IC socket,
4C type can be used with 2 sets of 14 pin IC sockets
- Amber sealed types and available
- Gold-cap silver palladium types available for 2 Form C type
- Bifurcated contacts are standard.

SPECIFICATIONS**Contact**

Arrangement	1 Form C, 2 Form C, 4 Form C
Initial contact resistance, max. (By voltage drop 6 V DC 1 A)	50 mΩ
Contact material	Gold-clad silver
Rating (resistive)	
Max. switching power	60 W, 125 VA
Max. switching voltage	220 V DC, 250 V AC
Max. switching current	2 A DC, AC
Max. carrying current	3 A DC, AC
UL/CSA rating	0.6 A 125 V AC 0.6 A 110 V DC 2 A 30 V DC

Expected life (min. operations)	
Mechanical (at 600 cpm)	10 ⁸ (1 Form C 2 coil latching type: 10 ⁷)
Electrical 2 A 30 V DC resistive	5 × 10 ⁵
1 A 30 V DC resistive	2 × 10 ⁶

*Gold capped silver-palladium contact also available for 2 Form C
10⁷ operations at 0.1 A 50 V DC resistive

Coil (polarized) (at 25°C 77°F)


"M" type	Single side stable	Minimum operating power	Approx. 200 mW
		Nominal operating power	Approx. 400 mW
	1 coil latching	Minimum set and reset power	Approx. 90 mW
		Nominal set and reset power	Approx. 180 mW
"S" type	2 coil latching	Minimum set and reset power	Approx. 180 mW
		Nominal set and reset power	Approx. 360 mW
	Single side stable	Minimum operating power	Approx. 100 mW (128 mW)*
		Nominal operating power	Approx. 200 mW
"S" type	1 coil latching	Minimum set and reset power	Approx. 45 mW (58 mW)*
		Nominal set and reset power	Approx. 90 mW
	2 coil latching	Minimum set and reset power	Approx. 90 mW (115 mW)*
		Nominal set and reset power	Approx. 180 mW

*For 1 Form C high sensitive types.

Characteristics (at 25°C 77°F, 50% Relative humidity)

Max. operating speed	20 cpm at rated load 50 cps at low level load
Operate time* (at nominal voltage)	Min. 10 msec. (Approx. 3 msec.)
Release time* (at nominal voltage)	Min. 5 msec. (Approx. 2 msec.)
Set time (latching) (at nominal voltage)	Approx. 3 msec.
Reset time (latching) (at nominal voltage)	Approx. 3 msec.
Initial breakdown voltage	(DS1-S type) 500 Vrms (Other types) 1,000 Vrms
Between open contacts	—
Between contact sets	1,000 Vrms
Between contacts and coil	1,500 Vrms
Initial insulation resistance	Min. 1,000 MΩ (at 500 V DC)
FCC** surge voltage between contacts and coil	1,500 V (Except DS1-S type)
Temperature rise (at nominal voltage)*	Max. 65°C
Ambient temperature	-40°C to +70°C
Shock resistance	Functional 1C, 2C: Min. 490 m/s ² (50 G) 4C: Min. 294 m/s ² (30 G)
	Destructive Min. 980 m/s ² (100 G)
Vibration resistance	Functional 196 m/s ² (20 G), 10 to 55 Hz at double amplitude of 3.3 mm
	Destructive 294 m/s ² (30 G), 10 to 55 Hz at double amplitude of 5 mm
Unit weight	1 Form C: Approx. 3.2 g
	2 Form C: Approx. 4 g
	4 Form C: Approx. 7 g

* Excluding contact bounce time
**FCC (Federal Communication Commission) requests following standard as Breakdown Voltage specification.

**ORDERING INFORMATION**Ex. DS 2 E — M L2 — DC 48V — R

Contact arrangement	Classification of type	Sensitivity	Operating function	Coil voltage
1: 1 Form C	Nil: Standard type	M: 400 mW nominal operating power	Nil: Single side stable	DC 1.5, 3, 5, 6,
2: 2 Form C	E: Amber sealed type	S: 200 mW nominal operating power	L: 1 coil latching	9, 12, 24, 48 V
4: 4 Form C			L2: 2 coil latching	

(Notes) 1. *Reverse polarity types available (Add suffix -R)

2. Standard packing: Carton: 50 pcs. Case: 500 pcs.

TYPICAL APPLICATIONS

- Telecommunication equipment
- Office equipment
- Computer peripherals
- Security equipment
- Measuring instrumentation

TYPES AND COIL DATA at 20°C 68°F

Single side stable

	Nominal voltage, V DC	Pick-up voltage, V DC (max.)	Drop-out voltage, V DC (min.)	Maximum allowable, V DC (at 50°C 122°F)	Coil resistance, Ω ($\pm 10\%$)
"M" type	1.5	1.05	0.15	1.8 2.25	5.63
	3	2.1	0.3	3.6 4.5	22.5
	5	3.5	0.5	6 7.5	62.5
	6	4.2	0.6	7.2 9	90
	9	6.3	0.9	10.8 13.5	203
	12	8.4	1.2	14.4 18	360
	24	16.8	2.4	28.8 36	1440
	48	33.6	4.8	57.6 72	5760
"S" type	1.5	1.2 1.05	0.15	2.4 3	11.3
	3	2.4 2.1	0.3	4.8 6	45
	5	4.0 3.5	0.5	8.0 10	125
	6	4.8 4.2	0.6	9.6 12	180
	9	7.2 6.3	0.9	14.4 18	405
	12	9.6 8.4	1.2	19.2 24	720
	24	19.2 16.8	2.4	38.4 48	2880
	48	38.4 33.6	4.8	76.8 96	11520

1 coil latching

	Nominal voltage, V DC	Reset Set, V DC (max.)	Maximum allowable, V DC (at 50°C 122°F)	Coil resistance, Ω ($\pm 10\%$)
"M" type	1.5	1.05	1.8 2.25	12.5
	3	2.1	3.6 4.5	50
	5	3.5	6 7.5	139
	6	4.2	7.2 9	200
	9	6.3	10.8 13.5	450
	12	8.4	14.4 18	800
	24	16.8	28.8 36	3200
	48	33.6	57.6 72	12800
"S" type	1.5	1.2 1.05	2.4 3	25
	3	2.4 2.1	4.8 6	100
	5	4.0 3.5	8.0 10	278
	6	4.8 4.2	9.6 12	400
	9	7.2 6.3	14.4 18	900
	12	9.6 8.4	19.2 24	1600
	24	19.2 16.8	38.4 48	6400
	48	38.4 33.6	76.8 96	25600


2 coil latching

	Nominal voltage, V DC	Reset Set, V DC (max.)	Maximum allowable, V DC (at 50°C 122°F)	Coil resistance, Ω ($\pm 10\%$)	
"M" type	1.5	1.05	1.8 2.25	6.25	
	3	2.1	3.6 4.5	25	
	5	3.5	6 7.5	69.4	
	6	4.2	7.2 9	100	
	9	6.3	10.8 13.5	225	
	12	8.4	14.4 18	400	
	24	16.8	28.8 36	1600	
	48	33.6	57.6 72	6400	
"S" type	1.5	1.2 1.05	2.4 3	12.5	
	3	2.4 2.1	4.8 6	50	
	5	4.0 3.5	8.0 10	139	
	6	4.8 4.2	9.6 12	200	
	9	7.2 6.3	14.4 18	450	
	12	9.6 8.4	19.2 24	800	
	24	19.2 16.8	38.4 48	3200	
	48	38.4 33.6	76.8 96	12800	

*Top: 1 Form C
Bottom: 2, 4 Form C

DIMENSIONS


1 Form C General tolerance: $\pm 0.3 \pm 0.12$
Single side stable & 1 coil latching




PC board pattern (Copper-side view)

Tolerance: $\pm 0.1 \pm 0.04$

Single side stable & 1 coil latching



2 coil latching




Schematic (Bottom view)

• A polarity bar showing the relay direction can replace the schematic.

Single side stable

Deenergized condition



1 coil latching




Diagram shows the "reset" position when terminals 1 and 6 are energized. Energize with reverse polarity to transfer contacts.

2 coil latching










Diagram shows the "reset" position when terminals 3 and 6 are energized. Energize terminals 1 and 3 to transfer contacts.

mm inch



mm inch



OPERATING PRINCIPLE - 4 Form C

DS4 (Single side stable)

Fig. 1 Deenergized position




Fig. 2 Energized position




Fig. 1 shows the deenergized position of single side stable versions. Concaves both in yoke (1) and yoke (2) create an unbalance of the magnetic circuit. Therefore the armature is attracted to the yoke (1) and yoke (2) as shown due to the magnetic flux of the permanent magnet.

Energized condition is illustrated in Fig. 2. When the armature is energized as shown, the magnetic repulsion-attraction between the yokes takes place rotating the armature. When the power is removed from the coil, contacts return to the original stage as shown in Fig. 1.

CONSTRUCTION - 4 Form C

Maximum reliability in a high density simplified design

